

# Nebraska Ethanol Board TIER I QUALIFIED FACILITY SPCC PLAN TEMPLATE



#### Instructions to Complete this Template

This template is intended to help the owner or operator of a Tier I qualified facility develop a self-certified Spill Prevention, Control, and Countermeasure (SPCC) Plan. To use this template, your facility must meet all of the applicability criteria of a Tier I qualified facility listed under §112.3(g)(1) of the SPCC rule and/or shown in the SPCC qualification flowchart. This template provides SPCC rule requirement necessary for a Tier I qualified facility, which you must address and implement. If you have a situation that does not fit into this template, please consult the EPA Tier I template (EPA Tier I SPCC Template) and complete that form.

You may use this template to comply with the SPCC regulation or use it as a model and modify it as necessary to meet your facility-specific needs. If you modify the template, your Plan must include a section cross-referencing the location of each applicable requirement of the SPCC rule and you must ensure that your Plan is an equivalent Plan that meets all applicable rule requirements of 40 CFR 112.6(a)(3).

You may complete this template either electronically or by hand on a printed copy. This document is a reformatted version of the template found in Appendix G of 40 CFR part 112.<sup>a</sup> No substantive changes have been made. Please note that a "Not Applicable" ("N/A") column has been added to both Table G-10 (General Rule Requirements for Onshore Facilities) and Table G-11 (General Rule Requirements for Onshore Oil Production Facilities). The "N/A" column should help you complete your self-certification when a required rule element does not apply to your facility. Use of the "N/A" column is optional and is not required by rule.

All Tier I qualified facility self-certifiers must complete Sections I, II, and III. Additionally, the owner or operator of an:

• Onshore facility (excluding production) must complete Section A.

Complete and include with your Plan the appropriate attachments. You should consider printing copies of the attachments for use in implementing the SPCC Plan (e.g. Attachment 3.1 - Inspection Log & Schedule; Attachment 4 - Discharge Notification Form).

To complete the template, check the box next to the requirement to indicate that it has been adequately addressed. Either write "N/A" in the column or check the box under the "N/A" column to indicate those requirements that are not applicable to the facility. Where a section requires a description or listing, write in the spaces provided (or attach additional descriptions if more space is needed).

Below is a key for the colors used in the section headers:

Sections I, II, and III: Required for all Tier I qualified facilities

Section A: Onshore facilities (excluding production)

Attachments: 1 - Five Year Review and Technical Amendment Logs
2 - Oil Spill Contingency Plan and Checklist
3 - Inspections, Dike Drainage and Personnel Training Logs
4 - Discharge Notification Form

After you have completed all appropriate sections, certify and date your Plan, and then implement it by the compliance date. Conduct inspections and tests in accordance with the written procedures that you have developed for your facility. You must keep with the SPCC Plan a record of these inspections and tests, signed by the appropriate supervisor or inspector, for a period of three years.

Do not forget to periodically review your Plan (at least once every five years) or to update it when you make changes to your facility. You must prepare amendments within six months of the facility change, and implement them as soon as possible, but not later than six months following preparation of any amendment.

In the event that your facility releases oil to navigable waters or adjoining shorelines, immediately call the National Response Center (NRC) at 1-800-424-8802. The NRC is the federal government's centralized reporting center, which is staffed 24 hours per day by U.S. Coast Guard personnel.

<sup>&</sup>lt;sup>a</sup> Please note that the use of this template is not mandatory for a Tier I qualified facility. You may also meet the SPCC Plan requirement by preparing a satisfactory Tier II qualified facility Plan, preparing a satisfactory Plan that is certified by a Professional Engineer, or by developing an equivalent Plan for a Tier I qualified facility. Further information on the requirements of these methods can be found in 40 CFR part 112.6(a)(1). If you use any of these alternative methods you must include a cross reference in your Plan that shows how the equivalent Plan meets all applicable 40 CFR part 112 requirements.

This template constitutes the SPCC Plan for the facility, when completed and signed by the owner or operator of a facility that meets the applicability criteria in §112.3(g)(1). This template addresses the requirements of 40 CFR part 112.

#### **Tier I Qualified Facility SPCC Plan**

Maintain a complete copy of the Plan at the facility if the facility is normally attended at least four hours per day, or for a facility attended fewer than four hours per day, at the nearest field office. When making operational changes at a facility that are necessary to comply with the rule requirements, the owner/operator should follow state and local requirements (such as for permitting, design and construction) and obtain professional assistance, as appropriate.

#### **Facility Description**

Facility Name			
Facility Address			
City	State	ZIP	
County	Tel. Number _( ) -		
Owner or Operator Name			
Owner or Operator Address			
City	State	ZIP	
County	Tel. Number ( ) -		

#### I. Self-Certification Statement (§112.6(a)(1))

The owner or operator of a facility certifies that each of the following is true in order to utilize this template to comply with the SPCC requirements:

certify that the following is accurate:

- 1. I am familiar with the applicable requirements of 40 CFR part 112;
- 2. I have visited and examined the facility;
- 3. This Plan was prepared in accordance with accepted and sound industry practices and standards;
- 4. Procedures for required inspections and testing have been established in accordance with industry inspection and testing standards or recommended practices;
- 5. I will fully implement the Plan;
- 6. This facility meets the following qualification criteria (under §112.3(g)(1)):
  - a. The aggregate aboveground oil storage capacity of the facility is 10,000 U.S. gallons or less; and
  - b. The facility has had no single discharge as described in §112.1(b) exceeding 1,000 U.S. gallons and no two discharges as described in §112.1(b) each exceeding 42 U.S. gallons within any twelve month period in the three years prior to the SPCC Plan self-certification date, or since becoming subject to 40 CFR part 112 if the facility has been in operation for less than three years (not including oil discharges as described in §112.1(b) that are the result of natural disasters, acts of war, or terrorism); and
  - c. There is no individual oil storage container at the facility with an aboveground capacity greater than 5,000 U.S. gallons.
- 7. This Plan does not deviate from any requirement of 40 CFR part 112 as allowed by §112.7(a)(2) (environmental equivalence) and §112.7(d) (impracticability of secondary containment) or include any measures pursuant to §112.9(c)(6) for produced water containers and any associated piping;
- 8. This Plan and individual(s) responsible for implementing this Plan have the full approval of management and I have committed the necessary resources to fully implement this Plan.

Facility Name:	

Ver. 2.0 8/9/16

I also understand my other obligations relating to the storage of oil at this facility, including, among others:

- 1. To report any oil discharge to navigable waters or adjoining shorelines to the appropriate authorities. Notification information is included in this Plan.
- 2. To review and amend this Plan whenever there is a material change at the facility that affects the potential for an oil discharge, and at least once every five years. Reviews and amendments are recorded in an attached log [See Five Year Review Log and Technical Amendment Log in Attachments 1.1 and 1.2.]
- 3. Optional use of a contingency plan. A contingency plan:
  - a. May be used in lieu of secondary containment for qualified oil-filled operational equipment, in accordance with the requirements under §112.7(k), and;
  - b. Must be prepared for flowlines and/or intra-facility gathering lines which do not have secondary containment at an oil production facility, and;
  - c. Must include an established and documented inspection or monitoring program; must follow the provisions of 40 CFR part 109; and must include a written commitment of manpower, equipment and materials to expeditiously remove any quantity of oil discharged that may be harmful. If applicable, a copy of the contingency plan and any additional documentation will be attached to this Plan as Attachment 2.

I certify that I have satisfied the requirement to prepare and implement a Plan under §112.3 and all of the requirements under §112.6(a). I certify that the information contained in this Plan is true.

Signature	Title: _				 -
Name	Date:	/	/ 20		

# II. Record of Plan Review and Amendments Five Year Review (§112.5(b)):

Complete a review and evaluation of this SPCC Plan at least once every five years. As a result of the review, amend this Plan within six months to include more effective prevention and control measures for the facility, if applicable. Implement any SPCC Plan amendment as soon as possible, but no later than six months following Plan amendment. Document completion of the review and evaluation, and complete the Five Year Review Log in Attachment 1.1. If the facility no longer meets Tier I qualified facility eligibility, the owner or operator must revise the Plan to meet Tier II qualified facility requirements, or complete a full PE certified Plan.

Table G-1 Technical Amendments (§§112.5(a), (c) and 112.6(a)(2))	
This SPCC Plan will be amended when there is a change in the facility design, construction, operation, or maintenance that materially affects the potential for a discharge to navigable waters or adjoining shorelines. Examples include adding or removing containers, reconstruction, replacement, or installation of piping systems, changes to secondary containment systems, changes in product stored at this facility, or revisions to standard operating procedures.	
Any technical amendments to this Plan will be re-certified in accordance with Section I of this Plan template. [§112.6(a)(2)] [See Technical Amendment Log in Attachment 1.2]	

-acility Name:	

Tier I Qualified Facility SPCC Plan

# III. Plan Requirements

# 1. Oil Storage Containers (§112.7(a)(3)(i)):

Facility Name:

Table G-2 Oil Storage Containers and Capacities  This table includes a complete list of all oil storage containers (aboveground containers <sup>a</sup> and completely buried tanks <sup>b</sup> ) with capacity of 55 U.S. gallons or more, unless otherwise exempt from the rule. For mobile/portable containers, an estimated number of containers, types of oil, and anticipated capacities are provided.				
Oil Storage Container (indicate whether	Type of Oil	Shell Capacity (gall	ons)	
aboveground (A) or completely buried (B))	1900 01 011	Onen Capacity (gain	0113)	
Tota	l al Aboveground Storage Capacity <sup>c</sup>	gallo	ns	
	ompletely Buried Storage Capacity	gallo		
	Facility Total Oil Storage Capacity	gallo	ns	
Aboveground storage containers that must be included when calculating total facility oil storage capacity include: tanks and mobile of cortable containers; oil-filled operational equipment (e.g. transformers); other oil-filled equipment, such as flow-through process equipment. Exempt containers that are not included in the capacity calculation include: any container with a storage capacity of less than 55 gallons of oil; containers used exclusively for wastewater treatment; permanently closed containers; motive power containers; not-mix asphalt containers; heating oil containers used solely at a single-family residence; and pesticide application equipment or related mix containers.				
Although the criteria to determine eligibility for qualified facompletely buried tanks at a qualified facility are still subjectively are not counted toward the qualified facility applicability.	ct to the rule requirements and must be add			
Counts toward qualified facility applicability threshold.				
2. Secondary Containment and Oil Spill Con			:	
	ry Containment and Oil Spill Control			
Appropriate secondary containment and/or diversio containers, equipment, and transfer areas to prevent				
The entire secondary containment system, including				
constructed so that any discharge from a primary construction of the construction of t	ontainment system, such as a tank or p	pipe, will not escape		
the containment system before cleanup occurs. <sup>a</sup> Use one of the following methods of secondary containm	ent or its equivalent: (1) Dikes harms or re	ataining walls sufficiently		
mpervious to contain oil; (2) Curbing; (3) Culverting, gutter diversion ponds; (6) Retention ponds; or (7) Sorbent mater	rs, or other drainage systems; (4) Weirs, bo		Spill	

Page 3

Table G-4 below identifies the tanks and containers at the facility with the potential for an oil discharge; the mode of failure; the flow direction and potential quantity of the discharge; and the secondary containment method and containment capacity that is provided.

	Table G-4 Containers with Pote				
Area	Type of failure (discharge scenario)	Potential discharge volume (gallons)	Direction of flow for uncontained discharge	Secondary containment method s <sup>a</sup>	Secondary containment capacity (gallons)
ulk Storage Containers and Mobil	le/Portable Containers <sup>b</sup>				
Oil-filled Operational Equipment (e.	g., hydraulic equipment, transformers) <sup>c</sup>	<u> </u>			<u> </u>
on mica operational Equipment (c.	g., ny dradne equipment, transformers)				
Product Transfer Areas (location w	here oil is loaded to or from a container, pipe or	other piece of e	equipment.)		
,	, , ,		<u> </u>		

<sup>&</sup>lt;sup>a</sup> Use one of the following methods of secondary containment or its equivalent: (1) Dikes, berms, or retaining walls sufficiently impervious to contain oil; (2) Curbing; (3) Culverting, gutters, or other drainage systems; (4) Weirs, booms, or other barriers; (5) Spill diversion ponds; (6) Retention ponds; or (7) Sorbent materials.

<sup>&</sup>lt;sup>b</sup> For storage tanks and bulk storage containers, the secondary containment capacity must be at least the capacity of the largest container plus additional capacity to contain rainfall or other precipitation.

<sup>&</sup>lt;sup>c</sup> For oil-filled operational equipment: Document in the table above if alternative measures to secondary containment (as described in §112.7(k)) are implemented at the facility.

3. Inspections, Testing, Recordkeeping and Personnel Training (§§112.7(e) and (f), 112.8(c)(6) and (d)(4), 112.9(c)(3), 112.12(c)(6) and (d)(4)):

Table G-5 Inspections, Testing, Recordkeeping and Personnel Training

An inspection and/or testing program is implemented for all aboveground bulk storage containers and piping at this facility. [ $\S\S112.8(c)(6)$ and $(d)(4)$ , $112.9(c)(3)$ , $112.12(c)(6)$ and $(d)(4)$ ]	
The following is a description of the inspection and/or testing program (e.g. reference to industry standard utilized	
scope, frequency, method of inspection or test, and person conducting the inspection) for all aboveground bulk st containers and piping at this facility:	orage
Inspections, tests, and records are conducted in accordance with written procedures developed for the facility.	
Records of inspections and tests kept under usual and customary business practices will suffice for purposes of this paragraph. [§112.7(e)]	
A record of the inspections and tests are kept at the facility or with the SPCC Plan for a period of three years.	П
[§112.7(e)] [See Inspection Log and Schedule in Attachment 3.1]	
Inspections and tests are signed by the appropriate supervisor or inspector. [§112.7(e)]	
Personnel, training, and discharge prevention procedures [§112.7(f)]  Oil-handling personnel are trained in the operation and maintenance of equipment to prevent discharges;	
discharge procedure protocols; applicable pollution control laws, rules, and regulations; general facility	
operations; and, the contents of the facility SPCC Plan. [§112.7(f)]  A person who reports to facility management is designated and accountable for discharge prevention.	
[§112.7(f)]	
Name/Title:	
Discharge prevention briefings are conducted for oil-handling personnel annually to assure adequate	
understanding of the SPCC Plan for that facility. Such briefings highlight and describe past reportable discharges or failures, malfunctioning components, and any recently developed precautionary measures.	]
[§112.7(f)]	
[See Oil-handling Personnel Training and Briefing Log in Attachment 3.4]	

Tier I Qualified Facility SPCC Plan

# 4. Security (excluding oil production facilities) §112.7(g):

Facility Name:

The following is a description of how you secure and control access to the oil handling, processing and storage a	
secure master flow and drain valves; prevent unauthorized access to starter controls on oil pumps; secure out-of service and loading/unloading connections of oil pipelines; address the appropriateness of security lighting to bot prevent acts of vandalism and assist in the discovery of oil discharges:	-
5. Emergency Procedures and Notifications (§112.7(a)(3)(iv) and 112.7(a)(5)):  Table G-7 Description of Emergency Procedures and Notifications  The following is a description of the immediate actions to be taken by facility personnel in the event of a discharg navigable waters or adjoining shorelines [§112.7(a)(3)(iv) and 112.7(a)(5)]:	e to
Table G-7 Description of Emergency Procedures and Notifications  The following is a description of the immediate actions to be taken by facility personnel in the event of a discharg	e to
Table G-7 Description of Emergency Procedures and Notifications  The following is a description of the immediate actions to be taken by facility personnel in the event of a discharg	e to
The following is a description of the immediate actions to be taken by facility personnel in the event of a discharg	e to
Table G-7 Description of Emergency Procedures and Notifications  The following is a description of the immediate actions to be taken by facility personnel in the event of a discharg	e to

Page 6

**Table G-6 Implementation and Description of Security Measures** 

Security measures are implemented at this facility to prevent unauthorized access to oil handling, processing,

# 6. Contact List (§112.7(a)(3)(vi)):

Table G-8 Contact List				
Contact Organization / Person	Telephone Number			
National Response Center (NRC)	1-800-424-8802			
Cleanup Contractor(s)				
Key Facility Personnel	•			
Designated Person Accountable for Discharge Prevention:	Office:			
	Emergency:			
	Office:			
	Emergency:			
	Office:			
	Emergency:			
	Office:			
	Emergency:			
State Oil Pollution Control Agencies				
Other State, Federal, and Local Agencies				
Local Fire Department				
Local Police Department				
Hospital				
Other Contact References (e.g., downstream water intakes or neighboring facilities)				

#### 7. NRC Notification Procedure (§112.7(a)(4) and (a)(5)):

Table G-9 NRC Notification Procedure				
In the event of a discharge of oil to navigable waters or adjoining shorelines, the following information identified				
in Attachment 4 will be provided to the National Response Center immediately following identification of a		Ш		
discharge to navigable waters or adjoining shorelines [Se	e Discharge Notification Form in Attachment 4]:			
[§112.7(a)(4)]				
<ul> <li>The exact address or location and phone</li> </ul>	<ul> <li>Description of all affected media;</li> </ul>			
number of the facility;  • Cause of the discharge;				
<ul> <li>Date and time of the discharge;</li> <li>Any damages or injuries caused by the discharge</li> </ul>		e;		
<ul> <li>Type of material discharged;</li> <li>Actions being used to stop, remove, and mitigate the</li> </ul>		the		
• Estimate of the total quantity discharged; effects of the discharge;				
<ul> <li>Estimate of the quantity discharged to navigable</li> <li>Whether an evacuation may be needed; and</li> </ul>				
waters;	<ul> <li>Names of individuals and/or organizations who h</li> </ul>	ave		
Source of the discharge:  also been contacted				

#### 8. SPCC Spill Reporting Requirements (Report within 60 days) (§112.4):

Submit information to the EPA Regional Administrator (RA) and the appropriate agency or agencies in charge of oil pollution control activities in the State in which the facility is located within 60 days from one of the following discharge events:

A single discharge of more than 1,000 U.S. gallons of oil to navigable waters or adjoining shorelines or Two discharges to navigable waters or adjoining shorelines each more than 42 U.S. gallons of oil occurring within any twelve month period

#### You must submit the following information to the RA:

- (1) Name of the facility;
- (2) Your name;
- (3) Location of the facility;
- (4) Maximum storage or handling capacity of the facility and normal daily throughput;
- (5) Corrective action and countermeasures you have taken, including a description of equipment repairs and replacements;
- (6) An adequate description of the facility, including maps, flow diagrams, and topographical maps, as necessary;
- (7) The cause of the reportable discharge, including a failure analysis of the system or subsystem in which the failure occurred; and
- (8) Additional preventive measures you have taken or contemplated to minimize the possibility of recurrence
- (9) Such other information as the Regional Administrator may reasonably require pertinent to the Plan or discharge

NOTE: Complete one of the following sections (A) as appropriate for the facility type.

as appropriate for the facility type.

# A. Onshore Facilities (excluding production) (§§112.8(b) through (d), 112.12(b) through (d)):

The owner or operator must meet the general rule requirements as well as requirements under this section. Note that not all provisions may be applicable to all owners/operators. For example, a facility may not maintain completely buried metallic storage tanks installed after January 10, 1974, and thus would not have to abide by requirements in §§112.8(c)(4) and 112.12(c)(4), listed below. In cases where a provision is not applicable, write "N/A".

Table G-10 General Rule Requirements for Onshore Facilities		N/A
Drainage from diked storage areas is restrained by valves to prevent a discharge into the drainage		
system or facility effluent treatment system, except where facility systems are designed to control such	Ш	
discharge. Diked areas may be emptied by pumps or ejectors that must be manually activated after		
inspecting the condition of the accumulation to ensure no oil will be discharged. [§§112.8(b)(1) and		
112.12(b)(1)]		
Valves of manual, open-and-closed design are used for the drainage of diked areas. [§§112.8(b)(2) and		
112.12(b)(2)]		
The containers at the facility are compatible with materials stored and conditions of storage such as		
pressure and temperature. [§§112.8(c)(1) and 112.12(c)(1)]		
Secondary containment for the bulk storage containers (including mobile/portable oil storage containers)		
holds the capacity of the largest container plus additional capacity to contain precipitation. Mobile or		
portable oil storage containers are positioned to prevent a discharge as described in §112.1(b).		
[§112.6(a)(3)(ii)]  If uncontaminated rainwater from diked areas drains into a storm drain or open watercourse the following		
procedures will be implemented at the facility: [§§112.8(c)(3) and 112.12(c)(3)]		
Bypass valve is normally sealed closed		
Retained rainwater is inspected to ensure that its presence will not cause a discharge to		
navigable waters or adjoining shorelines		
Bypass valve is opened and resealed under responsible supervision		
Adequate records of drainage are kept [See Dike Drainage Log in Attachment 3.3]		
For completely buried metallic tanks installed on or after January 10, 1974 at this facility [§§112.8(c)(4)		
and 112.12(c)(4)]:		
Tanks have corrosion protection with coatings or cathodic protection compatible with local soil		
conditions.		
Regular leak testing is conducted.		
For partially buried or bunkered metallic tanks [§112.8(c)(5) and §112.12(c)(5)]:		
Tanks have corrosion protection with coatings or cathodic protection compatible with local soil		
conditions.		
Each aboveground bulk container is tested or inspected for integrity on a regular schedule and whenever		П
material repairs are made. Scope and frequency of the inspections and inspector qualifications are in	Ш	
accordance with industry standards. Container supports and foundations are regularly inspected.		
[See Inspection Log and Schedule and Bulk Storage Container Inspection Schedule in		
Attachments 3.1 and 3.2] [§112.8(c)(6) and §112.12(c)(6)(i)]		
Outsides of bulk storage containers are frequently inspected for signs of deterioration, discharges, or		
accumulation of oil inside diked areas. [See Inspection Log and Schedule in Attachment 3.1]	_	
[§§112.8(c)(6) and 112.12(c)(6)]		
For bulk storage containers that are subject to 21 CFR part 110 which are shop-fabricated, constructed of austenitic stainless steel, elevated and have no external insulation, formal visual inspection is conducted		
on a regular schedule. Appropriate qualifications for personnel performing tests and inspections are		
documented. [See Inspection Log and Schedule and Bulk Storage Container Inspection Schedule		
in Attachments 3.1 and 3.21 [\$112.12(c)(6)(ii)]		

Table G-10 General Rule Requirements for Onshore Facilities	N/A
Each container is provided with a system or documented procedure to prevent overfills for the container. Describe:	
Liquid level sensing devices are regularly tested to ensure proper operation [See Inspection Log and Schedule in Attachment 3.1]. [§112.6(a)(3)(iii)]	
Visible discharges which result in a loss of oil from the container, including but not limited to seams, gaskets, piping, pumps, valves, rivets, and bolts are promptly corrected and oil in diked areas is promptly removed. [§§112.8(c)(10) and 112.12(c)(10)]	
Aboveground valves, piping, and appurtenances such as flange joints, expansion joints, valve glands and bodies, catch pans, pipeline supports, locking of valves, and metal surfaces are inspected regularly. [See Inspection Log and Schedule in Attachment 3.1] [§§112.8(d)(4) and 112.12(d)(4)]	
Integrity and leak testing are conducted on buried piping at the time of installation, modification, construction, relocation, or replacement. [See Inspection Log and Schedule in Attachment 3.1] [§§112.8(d)(4) and 112.12(d)(4)]	

# **ATTACHMENT 1 – Five Year Review and Technical Amendment Logs**

### **ATTACHMENT 1.1 – Five Year Review Log**

I have completed a review and evaluation of the SPCC Plan for this facility, and will/will not amend this Plan as a result.

Review Date Table G-13 Review and Evaluation of SPCC Plan for Facility  Name and signature of person authorized to review this					
Review Date	Plan An	nendment	Name and signature of person authorized to review this		
	Will Amend	Will Not Amend	Plan		
	_	_			
	_	_			
		_			
	_	_			
	_	_			
	_	_			
		_			
		<u> </u>			
	_ <del>_</del>	_ <del>_</del>			

Any technical amendments to this Plan will be re-certified in accordance with Section I of this Plan template.

	Table G-15 Description and Certification	of Technical Amendments
Review	Table G-15 Description and Certification Description of Technical Amendment	Name and signature of person certifying this
Date		technical amendment

# Ver. 1-E-doc-3-18-10 **ATTACHMENT 1.2 – Technical Amendment Log**

## ATTACHMENT 2 - Oil Spill Contingency Plan and Checklist

An oil spill contingency plan and written commitment of resources is required for:

- Flowlines and intra-facility gathering lines at oil production facilities and
- Qualified oil-filled operational equipment which has no secondary containment.

An oil spill contingency plan meeting the provisions of 40 CFR part 109, as described below, and a written	
commitment of manpower, equipment and materials required to expeditiously control and remove any quantity	
of oil discharged that may be harmful is attached to this Plan.	

Complete the checklist below to verify that the necessary operations outlined in 40 CFR part 109 - Criteria for State, Local and Regional Oil Removal Contingency Plans - have been included.

Table G-15 Checklist of Development and Implementation Criteria for State, Local and Regional Oil Remo Contingency Plans (§109.5) <sup>a</sup>				
(a) Definition of the authorities, responsibilities and duties of all persons, organizations or agencies which are to be involved in planning or directing oil removal operations.				
(b) Establishment of notification procedures for the purpose of early detection and timely notification of an oil discharge including:				
<ul><li>(1) The identification of critical water use areas to facilitate the reporting of and response to oil discharges.</li><li>(2) A current list of names, telephone numbers and addresses of the responsible persons (with alternates) and organizations to be notified when an oil discharge is discovered.</li></ul>				
(3) Provisions for access to a reliable communications system for timely notification of an oil discharge, and the capability of interconnection with the communications systems established under related oil removal contingency plans, particularly State and National plans (e.g., NCP).				
(4) An established, prearranged procedure for requesting assistance during a major disaster or when the situation exceeds the response capability of the State, local or regional authority.				
(c) Provisions to assure that full resource capability is known and can be committed during an oil discharge situation including:				
(1) The identification and inventory of applicable equipment, materials and supplies which are available locally and regionally.				
(2) An estimate of the equipment, materials and supplies which would be required to remove the maximum oil discharge to be anticipated.				
(3) Development of agreements and arrangements in advance of an oil discharge for the acquisition of equipment, materials and supplies to be used in responding to such a discharge.				
(d) Provisions for well defined and specific actions to be taken after discovery and notification of an oil discharge including:				
(1) Specification of an oil discharge response operating team consisting of trained, prepared and available operating personnel.				
(2) Predesignation of a properly qualified oil discharge response coordinator who is charged with the responsibility and delegated commensurate authority for directing and coordinating response operations and who knows how to request assistance from Federal authorities operating under existing national and regional contingency plans.				
(3) A preplanned location for an oil discharge response operations center and a reliable communications system for directing the coordinated overall response operations.				
(4) Provisions for varying degrees of response effort depending on the severity of the oil discharge.				
(5) Specification of the order of priority in which the various water uses are to be protected where more than one water use may be adversely affected as a result of an oil discharge and where response operations may not be adequate to protect all uses.				
(6) Specific and well defined procedures to facilitate recovery of damages and enforcement measures as provided for by State and local statutes and ordinances.				

Page 14

Facility Name:	

<sup>&</sup>lt;sup>a</sup> The contingency plan must be consistent with all applicable state and local plans, Area Contingency Plans, and the National Contingency Plan (NCP)

## **ATTACHMENT 3.1 – Inspection Log and Schedule**

Table G-16 Inspection Log and Schedule  This log is intended to document compliance with §§112.6(a)(3)(iii), 112.8(c)(6), 112.8(d)(4), 112.9(b)(2), 112.9(c)(3), 112.9(d)(1), 112.9(d)(4), 112.12.(c)(6), and 112.12(d)(4), as applicable.					
Date of Inspection	Container / Piping / Equipment	Describe Scope (or cite Industry Standard)	Observations	Name/ Signature of Inspector	Records maintained separately <sup>a</sup>

Facility	Name:				
----------	-------	--	--	--	--

# **ATTACHMENT 3.2 – Bulk Storage Container Inspection Schedule – onshore facilities (excluding production):**

To comply with integrity inspection requirement for bulk storage containers, inspect/test each shop-built aboveground bulk storage container on a regular schedule in accordance with a recognized container inspection standard based on the minimum requirements in the following table.

Table G-17 Bulk Storage Container Inspection Schedule				
Container Size and Design Specification	Inspection requirement			
Portable containers (including drums, totes, and intermodal bulk containers (IBC))	Visually inspect monthly for signs of deterioration, discharges or accumulation of oil inside diked areas			
55 to 1,100 gallons with sized secondary containment 1,101 to 5,000 gallons with sized secondary containment and a means of leak detection <sup>a</sup>	Visually inspect monthly for signs of deterioration, discharges or accumulation of oil inside diked areas plus any annual inspection elements per industry inspection standards			
1,101 to 5,000 gallons with sized secondary containment and no method of leak detection <sup>a</sup>	Visually inspect monthly for signs of deterioration, discharges or accumulation of oil inside diked areas, plus any annual inspection elements and other specific integrity tests that may be required per industry inspection standards			

<sup>&</sup>lt;sup>a</sup> Examples of leak detection include, but are not limited to, double-walled tanks and elevated containers where a leak can be visually identified.

# **ATTACHMENT 3.3 – Dike Drainage Log**

			On an humana	Table G-18	Dike Drainage Log	
Date	Bypass valve sealed closed	Rainwater inspected to be sure no oil (or sheen) is visible	Open bypass valve and reseal it following drainage	Drainage activity supervised	Observations	Signature of Inspector

# **ATTACHMENT 3.4 – Oil-handling Personnel Training and Briefing Log**

	Table G-19 Oil-Handling Person	and Training and Briefing Log
Date	Table G-19 Oil-Handling Person Description / Scope	Attendees
Date	Description / Ocope	Attoriation
I	1	ı

# **ATTACHMENT 4 – Discharge Notification Form**

In the event of a discharge of oil to navigable waters or adjoining shorelines, the following information will be provided to the National Response Center [also see the notification information provided in Section 7 of the Plan]:

Table G-20 Information provided to the National Response Center in the Event of a Discharge			
Discharge/Discovery Date		Time	
Facility Name			
Facility Location (Address/Lat-			
Long/Section Township Range)			
Name of reporting individual		Telephone #	
Type of material discharged		Estimated total quantity	Gallons/Barrels
31		discharged	
Source of the discharge		Media affected	Soil
			☐ Water (specify)
			Water (speeliy)
			Other (specify)
Actions taken			
Damage or injuries	☐ No ☐ Yes (specify)	Evacuation needed?	☐ No ☐ Yes (specify)
Organizations and individuals	☐ National Response Center 800-424-8802 Time		
contacted	☐ Cleanup contractor (Specify) Time		
	☐ Facility personnel (Specify) Time		
	State Agency (Specify) Time		
Other (Specify) Time			